

Features

- Compatible with HDMI 1.3c
- Supports 2.5 Gbps signaling rate for 480i/p, 720i/p, and 1080i/p resolutions up to 12-bit color depth
- Integrated receiver termination
- Adaptive receiver equalization to accommodate to different input cable lengths
- DDC buffer link
- CEC buffer link
- Intra-pair skew < 40 ps
- Inter-pair skew < 65 ps
- **System Level ESD Protection Exceeds 8 kV (direct contact) for TMDS Inputs and DDC Interface**
- Single supply voltage, VCC= 3.3 V +/- 5%
- Controllable shutdown and standby modes for power saving
- Controllable logic states for HPD output
- 5-V tolerance on all side band signals
- 64-pin LQFP package
- **Green part** and 260 °C reflow rated

Applications

- Digital TV
- Digital projector
- Digital monitor
- Audio video receiver

Description

The AZHW271 is a 2-port High-Definition Multimedia Interface (HDMI) or DVI switch which allows up to 2 HDMI or DVI ports to be switched to a single display terminal. Four TMDS channels, one hot plug detector, and a digital display control (DDC) interface are supported on each port. Each TMDS channel allows signaling rates up to 2.5 Gbps to allow 1080p resolution in 12-bit color depth.

With three control pins, the AZHW271 can be operated at the shutdown mode. At this condition, all TMDS input terminations are disconnected and at the state of high impedance. Moreover, the DDC links are disabled due to that all internal devices are turned off and all HPD outputs are connected to the HPD_SINK. This allows the initiation of the HDMI physics address discovery process. Termination resistor (50-Ω), pulled up to VCC, are integrated at each TMDS receiver input. External terminations are not required as shown in Fig. 1.




Fig. 1 TMDS internal termination

The AZHW271 provides adaptive input equalization for different ranges of cable lengths. Each TMDS receiver owns frequency responsive equalization circuits. A 20k-ohm (recommended value) calibration resistor is tied to GND for EQ pin, the receiver with optimized equalization supports the connection in different range HDMI cables. Moreover, A 20k-ohm (recommended value) calibration resistor is tied to GND for RP1 (pin 9) pin, the receiver of port 1 with adaptive equalization supports the input connection in different range HDMI cables. Also, A 20k-ohm (recommended value) calibration resistor is tied to GND for RP2 (pin 3) pin, the receiver of port 2 with adaptive equalization supports the input


connection in different range HDMI cables. The AZHW271 supports two types of power saving operations. When a system is under shutdown mode and there is no digital audio/visual content from a connected source to minimize power consumption from TMDS inputs, outputs, and internal circuits. When a system is under standby mode (PS at logic high), only TMDS clock inputs, outputs and termination are turned on, and the selected DDC buffer link from the source to sink. At this state, the system can be quick recovery as the digital audio/visual content from a connected source. Otherwise, to filter supply noise, all VCC pins are recommended to have a 0.01 uF capacitor tied from each VCC pin to ground directly. For the ESD protection function, the AZHW271 is designed to withstand the ESD level (IEC61000-4-2) to contact mode 8 kV. For the requirements of application, a higher protection level is needed. The AZHW271

can provide TMDS pairs, DDC, and HPD pins' ESD levels (IEC61000-4-2) to contact mode 6 kV. And external ESD components are not required for the criteria of ESD contact mode 8 kV.

Furthermore, the AZHW271 also provides controllable states of HPD outputs. When HPD_ctl set high, all HPD outputs can follow HPD_SINK. For the V_{sdj} pin, it is recommended to be tied a 6.2-kΩ resistor (10% precision) to control the output swing to the HDMI compliance test.


Finally, the AZHW271 also integrates an HDMI compliant I/O to enable Consumer Electronics Control (CEC) in a DTV. The CEC I/O meets all HDMI compliance test and eliminates the need for additional external components. The device is characterized for operation from 0 °C to 70 °C.

Typical application






Circuit diagram



Pin Configuration



TERMINAL FUNCTIONS

TERMINAL		I/O	Description
NAME	NO.		
A11, A12, A13, A14	39, 42, 45, 48	I	Source port 1 TMDS positive inputs
A21, A22, A23, A24	54, 57, 60, 63	I	Source port 2 TMDS positive inputs
B11, B12, B13, B14	38, 41, 44, 47	I	Source port 1 TMDS negative inputs
B21, B22, B23, B24	53, 56, 59, 62	I	Source port 2 TMDS negative inputs
GND	15, 22, 28, 43, 58	---	Ground
EQ	34	I	TMDS input equalization calibration
PS	13	I	Power saving selector PS= high---standby mode PS= low---normal mode
HPD_ctl	11	I	HPD output selector HPD_ctl= high---all HPD output follows HPD_SINK HPD_ctl=low---only selected HPD output follows HPD_SINK
HPD1	35	O	Source port 1 hot plug detector output
HPD2	50	O	Source port 2 hot plug detector output
HPD_SINK	31	I	Sink port hot plug detector input
SCL1	37	I/O	Source port 1 DDC I ² C clock line
SCL2	52	I/O	Source port 2 DDC I ² C clock line
SCL_SINK	29	I/O	Sink port DDC I2C clock line
SDA1	36	I/O	Source port 1 DDC I ² C data line
SDA2	51	I/O	Source port 2 DDC I ² C data line
SDA_SINK	30	I/O	Sink port DDC I ² C data line
S1, S2	32,33	I	Source selector
VCC	6, 12, 19, 25, 40, 46, 55, 61	---	Power supply
Vsadj	16	I	TMDS compliant voltage swing control
CEC_A	10	I/O	Source port 1,2,3,4 CEC line
CEC_D	14	I/O	Sink port CEC line
Y1, Y2, Y3, Y4	26, 23, 20, 17	O	Sink port TMDS positive outputs
Z1, Z2, Z3, Z4	27, 24, 21, 18	O	Sink port TMDS negative outputs
RP1	9	I	Port 1 calibration resistor
RP2	3	I	Port 2 calibration resistor
Rp3	49	I	TMDS input equalization calibration
NC	1, 2, 4, 5, 7, 8, 64	---	NC pins



Table-1-1: Source Selection Lookup (Normal operation)

CONTROL PINS				I/O SELECTED		HOT PLUG DETECT STATUS	
S1	S2	PS	HPD _ctl	Y/Z	SCL_sink SDA_sink	HPD1	HPD2
H	H	L	L	A1/B1 Terminations of A2/B2 are disconnected	SCL1 SDA1	HPD_SINK	L
L	H	L	L	A2/B2 Terminations of A1/B1 are disconnected	SCL2 SDA2	L	HPD_SINK

Note. H: logic high; L: logic low;

Table-1-2: Source Selection Lookup (Normal operation)

CONTROL PINS				I/O SELECTED		HOT PLUG DETECT STATUS	
S1	S2	PS	HPD _ctl	Y/Z	SCL_sink SDA_sink	HPD1	HPD2
H	H	L	H	A1/B1 Terminations of A2/B2, are disconnected	SCL1 SDA1	HPD_SINK	HPD_SINK
L	H	L	H	A2/B2 Terminations of A1/B1 are disconnected	SCL2 SDA2	HPD_SINK	HPD_SINK

Note. H: logic high; L: logic low;



Table-1-3: Source Selection Lookup (Standby mode)

CONTROL PINS				I/O SELECTED		HOT PLUG DETECT STATUS	
S1	S2	PS	HPD _ctl	Y/Z	SCL_sink SDA_sink	HPD1	HPD2
H	H	H	L	A11/B11 Terminations of A12, B12, A13, B13, A14, B14, A2n, B2n are disconnected	SCL1 SDA1	HPD_SINK	L
L	H	H	L	A21/B21 Terminations of A22, B22, A23, B23, A24, B24, A1n, B1n are disconnected	SCL2 SDA2	L	HPD_SINK

Note. H: logic high; L: logic low;

Table-1-4: Source Selection Lookup (Standby mode)

CONTROL PINS				I/O SELECTED		HOT PLUG DETECT STATUS	
S1	S2	PS	HPD _ctl	Y/Z	SCL_sink SDA_sink	HPD1	HPD2
H	H	H	H	A11/B11 Terminations of A12, B12, A13, B13, A14, B14, A2n, B2n are disconnected	SCL1 SDA1	HPD_SINK	HPD_SINK
L	H	H	H	A21/B21 Terminations of A22, B22, A23, B23, A24, B24, A1n, B1n are disconnected	SCL2 SDA2	HPD_SINK	HPD_SINK

Note. H: logic high; L: logic low;



Table-1-5: Source Selection Lookup (Shutdown mode)

CONTROL PINS				I/O SELECTED		HOT PLUG DETECT STATUS	
S1	S2	PS	HPD _ctl	Y/Z	SCL_sink SDA_sink	HPD1	HPD2
H	L	L	H	All Terminations are disconnected	Are pulled high by external pull-up termination	HPD_SINK	HPD_SINK

Note. H: logic high; L: logic low;

ABSOLUTE MAXIMUM RATINGS

			UNIT
Supply voltage range	VCC		-0.5V to 4V
Voltage range	Anm, Bnm		2.5V to 4V
	Ym, Zm, VSADJ, EQ, HPDn, PS, HPD_ctl, CEC_A, CEC_D		-0.5V to 4V
	SCLn, SCL_SINK, SDAn, SDA_SINK, HPD_SINK, S1, S2, S3		-0.5V to 5.5V
Electrostatic discharge	System level (direct contact) (1)	Anm, Bnm, SCLn, SDAn, HPDn,	+/- 6 KV
	Human body model (2)	Anm, Bnm, SCLn, SDAn, HPDn	+/- 8 KV
		All pins	+/- 4 KV
	Machine model (2)	All pins	+/- 200V
	Charged-device model (2)	All pins	+/- 1000V

*(1) System level: tested in accordance with IEC61000-4-2

*(2) Tested in accordance with JEDEC Standard 22

RECOMMENDED OPERATING CONDITIONS

	MIN	NOM	MAX	UNIT
VCC Supply voltage	3.135	3.3	3.465	V
T _A Operating free-air temperature	0	25	70	°C
TMDS differential pins				
V _{IC} Input common mode voltage	VCC-0.4		VCC+0.01	V
V _{ID} Receiver peak-to-peak differential input voltage	150		1560	mV _{P-P}
R _{VSADJ} Resistor for TMDS compliant voltage swing range		6.2		KΩ
RP _{1,2,3} Resistor for TMDS calibration		100		KΩ
EQ Resistor for TMDS equalization calibration		10		KΩ
AV _{CC} TMDS output termination voltage		3.3		V
R _T Termination resistance	45	50	55	Ω
Signaling rate	0		2.5	Gbps
Control pins (EQ, PS, HPD_ctl)				
V _{IH} LVTTL High-level input voltage	2		VCC	V
V _{IL} LVTTL Low-level input voltage	GND		0.8	V
DDC I/O pins				
V _{I(DDC)} DDC input voltage	GND		5.5	V
Status and source selector pins (S1, S2, HPD_SINK)				
V _{IH} LVTTL High-level input voltage	1.5		5.5	V
V _{IL} LVTTL Low-level input voltage	GND		0.8	V

Electrical Characteristics

Over recommended operating conditions (unless otherwise noted)

PARAMETER	TEST CONDITIONS	MIN	TYP (1)	MAX	UNIT
I _{CC} Supply current	R _T = 50 Ω V _{CC} = 3.3V AV _{CC} = 3.3V Data pattern = 2.5 Gbps Clock = 250 MHz	S1/S2= L/H H/H PS=L	200		mA
		S1/S2= H/L	5		mA
		S1/S2= L/H H/H PS=H	10		mA
TMDS DIFFERENTIAL PINS (A/B; Y/Z)					
V _{OH} Single-ended high-level output Voltage	R _T = 50 Ω V _{CC} = 3.3V AV _{CC} = 3.3V	AV _{CC} -10	AV _{CC}	AV _{CC} +10	mV
V _{OL} Single-ended low-level output voltage		AV _{CC} -700	AV _{CC} -560	AV _{CC} - 400	mV
V _{swing} Single-ended output swing voltage		400	560	700	mV
I _(os) Short circuit output current			11.5	14	mA
R _{INT} Input termination resistance	V _{IN} = 2.9 V	45	50	55	Ω
STATUS AND SOURCE SELECTOR PINS					
V _{IH} TTL High-level input voltage		2.5		5.5	V
V _{IL} TTL Low-level input voltage		GND		0.8	V



Electrical Characteristics (continued)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
DDC I/O PINS					
$C_{IO(sink)}$ Input/output capacitance	$V_{I(PP)} = 1V, 100\text{ kHz}$		10		pF
$V_{IH(sink)}$ High-level input voltage		2.0		5.5	V
$V_{IL(sink)}$ Low-level input voltage		GND		0.8	V
$C_{IO(port\ 1:4)}$ Input/output capacitance	$V_{I(PP)} = 1V, 100\text{ kHz}$		6		pF
$V_{IH(port\ 1:4)}$ High-level input voltage		2.0		5.5	V
$V_{IL(port\ 1:4)}$ low-level input voltage		GND		0.8	V
STATUS AND SOURCE SELECTOR PINS					
V_{IH} TTL High-level input voltage		2.5		5.5	V
V_{IL} TTL Low-level input voltage		GND		0.8	V

- (1) All typical values are at 25 °C and with a 3.3-V VCC supply.



SWITCHING CHARACTERISTICS

Over recommended operating conditions (unless otherwise noted)

PARAMETER	TEST CONDITIONS	MIN	TYP ⁽¹⁾	MAX	UNIT
TMDS DIFFERENTIAL PINS (Y/Z)					
t_{PLH} Propagation delay time, low-to-high-level output	$R_T = 50\ \Omega$ $AV_{CC} = 3.3V$ $Am/Bm\ (1)$ $= 250\ MHz\ clock$ $Am/Bm\ (2:4)$ $= 2.5\ Gbps\ pattern$		1200	1500	ps
t_{PHL} Propagation delay time, high-to-low-level output			1200	1500	ps
t_r Differential output signal rise time		75		240	ps
t_f Differential output signal fall time		75		240	ps
$t_{sk(p)}$ Pulse skew ($t_{PHL} - t_{PLH}$)			10	50	ps
$t_{sk(D)}$ Intra-pair differential skew			20	40	ps
$t_{sk(O)}$ Inter-pair differential skew			18	65	ps
$t_{jt(PP)}$ Peak-to-peak output jitter(Y1/Z1)			40	50	ps
$t_{jt(PP)}$ Peak-to-peak output jitter (Y2/Z2; Y3/Z3; Y4/Z4)			75	120	ps
t_{sx} Select to switch output			25	60	ns

***(1) All typical values are at 25°C and with a 3.3-V VCC supply.**




Mechanical Details

64-pin LQFP

PACKAGE DIAGRAMS


TOP VIEW



SYMBOL	DIMENSION IN MM			DIMENSION IN INCH		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A			1.60			0.063
A1	0.05		0.15	0.002		0.006
A2	1.35	1.40	1.45	0.053	0.055	0.057
b	0.17	0.20	0.23	0.007	0.008	0.009
c	0.09		0.16	0.004		0.006
e	0.50 BASIC			0.020 BASIC		
D	12.00 BASIC			0.472 BASIC		
D1	10.00 BASIC			0.394 BASIC		
E	12.00 BASIC			0.472 BASIC		
E1	10.00 BASIC			0.394 BASIC		
L	0.45	0.60	0.75	0.018	0.024	0.030
L1	1.00 REF.			0.039 REF.		
R1	0.08			0.003		
R	0.08		0.20	0.003		0.008
θ	0	3.5	7	0	3.5	7
θ1	0			0		
θ2	11	12	13	11	12	13
θ3	11	12	13	11	12	13
JEDEC	MS-026 (BCD)					

△*NOTES : DIMENSIONS " D1 " AND " E1 " DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE PROTRUSION IS 0.25 mm PER SIDE.
" D1 " AND " E1 " ARE MAXIMUM PLASTIC BODY SIZE DIMENSIONS INCLUDING MOLD MISMATCH.

SIDE VIEW



Marking Code

Part Number	Marking Code
AZHW271	AZHW271



Revision History

Revision	Modification Description
Revision 2011/05/09	Formal Release.